



**Product Highlights:**

- Wide beam angle up to 110°
- Integrated and slim design with the height of 35mm
- Four size options 4"/5"/6"/8"
- Full power range 8W/10W/16W/24W
- Long lifetime up to 30,000 hours
- IP40

## Light is extensive LEDCOMFO® Downlight V3

A latest, integrated designed indoor luminaire for large space illumination.

Light is OSRAM


**OSRAM**

## LEDCOMFO® Downlight V3




LEDCOMFO® Downlight V3 is the latest generation lighting solution for large space illumination. The slim and integrated body design provides high quality and safety based on 30,000 hours lifetime and all size options 4"/5"/6"/8".

### Dimensions



	8W	10W	16W	20W
ØD	120mm	150mm	175mm	225mm
H	35mm	35mm	35mm	35mm

### Photometrics



### Advantages & Benefits

#### Rigidity & safety

- 30,000hrs lifetime
- 1KV line-to-line surge protection
- IP40

#### Uniform and comfortable lighting experience

- Optimized optical design brings high uniformity
- Imported LED provides consistent color temperature
- CRI>80
- Wide beam angle 110°

#### Easy to install

- Wide mounting ring (10mm to 12.5mm) which can fit the dimensional deviation of installation in various retrofit projects
- Integrated design
- Slim design with the height of 35mm
- 100~140mm pre-wire

#### Full range to meet all applications request

- Four size options 4"/5"/6"/8"
- Full power range 8W/10W/16W/24W
- CCT 3000K/4000K/6500K

### Applications

- Commercial buildings
- Offices
- Public areas
- Warehouses and workshops

Product Reference	Ordering Code (EAN40)		V	W	Hz		K	lm			
LCM DL 8W 830 4IN V3 48X1 OSRAM	4052899596191	Warm White	220-240	8	50/60	110	3000	600	120	35	48
LCM DL 8W 840 4IN V3 48X1 OSRAM	4052899596214	Neutral White	220-240	8	50/60	110	4000	600	120	35	48
LCM DL 8W 865 4IN V3 48X1 OSRAM	4052899596238	Cold White	220-240	8	50/60	110	6500	600	120	35	48
LCM DL 10W 830 5IN V3 36X1 OSRAM	4052899596252	Warm White	220-240	10	50/60	110	3000	800	150	35	36
LCM DL 10W 840 5IN V3 36X1 OSRAM	4052899596276	Neutral White	220-240	10	50/60	110	4000	800	150	35	36
LCM DL 10W 865 5IN V3 36X1 OSRAM	4052899596290	Cold White	220-240	10	50/60	110	6500	800	150	35	36
LCM DL 16W 830 6IN V3 36X1 OSRAM	4052899596313	Warm White	220-240	16	50/60	110	3000	1360	175	35	36
LCM DL 16W 840 6IN V3 36X1 OSRAM	4052899596337	Neutral White	220-240	16	50/60	110	4000	1360	175	35	36
LCM DL 16W 865 6IN V3 36X1 OSRAM	4052899596351	Cold White	220-240	16	50/60	110	6500	1360	175	35	36
LCM DL 24W 830 8IN V3 32X1 OSRAM	4052899596375	Warm White	220-240	24	50/60	110	3000	2160	225	35	32
LCM DL 24W 840 8IN V3 32X1 OSRAM	4052899596399	Neutral White	220-240	24	50/60	110	4000	2160	225	35	32
LCM DL 24W 865 8IN V3 32X1 OSRAM	4052899596412	Cold White	220-240	24	50/60	110	6500	2160	225	35	32

Technical data subject to variation and change without notice.

OSRAM Lighting Solutions Asia Pacific

Sales enquiry: [lighting.solutions.apac@osram.com](mailto:lighting.solutions.apac@osram.com)  
[www.osram.asia/ls](http://www.osram.asia/ls)

