



Date: \_\_\_\_\_ Quantity: \_\_\_\_\_  
Company: \_\_\_\_\_  
Project: \_\_\_\_\_

## ProPoint™ SW 40W Wall Washer

The ProPoint SW 40W Wall Washer is an AC line powered, high brightness luminaire. The luminaire is controllable via DMX512. The system is connected using a daisy chain topology, allowing easy installation to form long run lengths. Remote Device Management (RDM) circuits are built into each luminaire that enables extensive control and monitoring of the entire installation.



### Product Specifications

Light Source	20 LED
Color Range	4000K/3000K
Beam Angles	15°, 25°, 35°
Luminous Flux	4000K - 2670 / 3000K - 2540
Efficacy	4000K - 66lm/W / 3000K - 63lm/W
Lumen Maintenance	L <sub>70</sub> @ 25°C 81,000 hours
Cover-Lens	(10mm) .39" Glass
Housing	Die Cast Aluminum
Adjustment Options	50° Forward, 80° Backward
Size	222mm x 165mm x 254mm (8.8"x6.5"x10")
Weight	3.8 kgs (8.4 lbs.)
Regulatory/Product Certifications	ETL, FCC, RoHS, ASTM B117-16, ANSI 3G, IK10
Operating Temperature	-30°C to +50°C (-22°F to +122°F)
Minimum Starting Temperature	-20°C (-4°F)
Storage Temperature	-40°C to +80°C (-40°F to +158°F)
Environment	IP66 Outdoor, Coastal Rated
Humidity	85%, non-condensing

### Electrical Specifications

Input Voltage <sup>1</sup>	120-277V <sub>AC</sub> 50/60Hz
Power Consumption	40W
Power Factor	≥ 0.9

### System Specifications

Power	AC Line
Control	DMX 512, RDM Enabled
Power Supply	Integrated

1. Auto-switching. Single phase (line, neutral and ground).

LED CHARACTERISTICS: Because LEDs are semiconductor devices, their performances are subject to inherent variability commonly found in semiconductor industry. To improve consistency in performance across the same product, LED manufacturers "sort" LEDs into bins according to different preset parameters, such as forward driving voltage, illumination, etc. Whereas binning is a sorting function, it is not a correction process. Inherent variability in the manufacturing process always results in different binning distributions according to different production lots. Traxon uses automatically binned LEDs on its products, thereby minimizing output variations within the model range.

As with all electronic devices, LED output degrades over time – a term called lumen depreciation. This also explains why it is nearly impossible to expect photometric performances of two LED products with different service life spans to be the same. The rate of LED degrade is a complicated function involving many factors, such as operating efficiency, duration of continuous operation and, more significantly, environmental conditions (ambient temperature for example). If allowed, working under optimal operating temperature range and with good ventilation, LED devices enjoy long service lives over conventional light sources. When using/installing LED devices, care should be taken to ensure that the devices will operate within the operating conditions specified in respective product literature.

Lumen measurement complies with LM-79-08 standard.  
Lumen maintenance is calculated based on LM-80 compliant measurement.

[www.traxontechnologies.com](http://www.traxontechnologies.com)

©2018 TRAXON TECHNOLOGIES - AN OSRAM BUSINESS. ALL RIGHTS RESERVED. TRAXON™ AND TX CONNECT® ARE TRADEMARKS OF TRAXON TECHNOLOGIES. U.S. PATENTS, E.U. PATENTS, JAPAN PATENTS, OTHER PATENTS PENDING. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

# ProPoint™ SW 40W Wall Washer


## Photometrics

### Source Specifications

LED Source	White
Beam Angle	15°


### Candela Distribution

### Light Output



Color Temperature	Luminous Flux (lm)	Candela Distribution @100%	Efficacy lm/W
4000K	2670	16273	75.98

### Illuminance at a Distance



- Vert.Spread: 17.9°
  - Horiz.Spread: 17.9°
- For fc divide by 10.7

For feet multiply by 3.28

# ProPoint™ SW 40W Wall Washer


## Photometrics

### Source Specifications

LED Source	White
Beam Angle	15°


### Candela Distribution

### Light Output




Color Temperature	Luminous Flux (lm)	Candela Distribution @100%	Efficacy lm/W
3000K	2540	15621	72.94

### Illuminance at a Distance



- Vert. Spread: 18°
  - Horiz. Spread: 18°
- For feet multiply by 3.28  
For fc divide by 10.7

- ProPoint fixtures ship with two cable whips: One cable whip for power input consisting of two wires plus a ground and one cable whip for DMX512 RDM input/output.



## General Notes

- All data cabling must adhere to ANSI E1.11-2008 (R2013) – Entertainment Technology – USITT DMX512-A, Asynchronous Serial Digital Data Transmission Standard for Controlling Lighting Equipment and Accessories.
- Fixture is RDM capable.
- Fixtures allow a universal input of 120VAC to 277VAC.
- Data termination shall utilize cage clamp terminal blocks, or equivalent. Wire nuts are not permissible and will void warranty.
- The method of line voltage termination, both for data and power, is at the discretion of the installing contractor, and or engineer. Splicing and/or joining of cables must adhere to all applicable electrical codes.
- Cables must be spliced/joined in a weatherproof enclosure/junction box, which is to be properly rated and provided by others.

# ProPoint™ SW 40W Wall Washer

Ordering

## Model Number

PP . W4 . 9 1 X 1 X X

ProPoint	Washer	Control	Channels	CCT	Cover Lens	Optic	Finish
		9: DMX	1: SW	3: 3000K	Clear	2: 15°	1: Gray
				4: 4000K		3: 25°	2: Black
						4: 35°	3: White

**traxon**cue  
AN OSRAM BUSINESS

[www.traxontechnologies.com](http://www.traxontechnologies.com)

**OSRAM**

© 2018 TRAXON TECHNOLOGIES - AN OSRAM BUSINESS. ALL RIGHTS RESERVED. TRAXON™, TX CONNECT®, ARE TRADEMARKS OF TRAXON TECHNOLOGIES. U.S. PATENTS, E.U. PATENTS, JAPAN PATENTS, OTHER PATENTS PENDING. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.