



**Product Highlights:**

- Compact and lightweight design
- High efficiency up to 130lm/W
- Robust Aluminum housing
- 50,000 hours lifetime
- Surfaced mounted and suspended

# Light is dependable Simplitz® Batten V3

Compact and lightweight design for indoor application.

Light is **OSRAM**

## Simplitz® Batten V3



Simplitz® Batten V3 was born in 2014 and this V3 is the most updated version of this attractive family. Still compact and lightweight design, but more reliable and higher efficient. Years evolution makes it the perfect solution for retail store, workshop, and other public area.

### Advantages & Benefits

#### Simplicity

- Compact and lightweight design
- Easy installation
- Direct replacement of previous generation

#### Efficiency

- Up to 130 lm/W, more than 60% energy saving

#### Reliability

- 50K hours lifespan
- Robust Aluminum housing with good thermal management

#### Flexibility

- 585mm/1170mm
- 16W/33W
- Surfaced mounted and suspended

### Dimensions


	4300 lm, 1170mm	2100 lm, 1170mm	2100 lm, 585mm
<b>L</b>	1170mm	1170mm	585mm
<b>W</b>	43mm	43mm	43mm
<b>H</b>	52mm	52mm	52mm
<b>D</b>	700mm-800mm	700mm-800mm	400mm-500mm

### Applications


- Hypermarket, retail stores
- Storage, warehouses
- Workshops
- Shopping malls

### Photometrics


16W, 600mm



16W, 1200mm



33W, 1200mm



Product Reference	Ordering Code (EAN40)		V	W	Hz	K	lm		$\frac{l}{b}$ [mm]	$\frac{h}{b}$ [mm]		
SIM BTN 16W 840 L600 SL V3 20X1 OSRAM	4062172048088	Neutral white	220-240	16	50 / 60	4000	2100	110	585	43	52	20
SIM BTN 16W 865 L600 SL V3 20X1 OSRAM	4062172048095	Cold white	220-240	16	50 / 60	6500	2100	110	585	43	52	20
SIM BTN 16W 840 L1200 SL V3 20X1 OSRAM	4062172048064	Neutral white	220-240	16	50 / 60	4000	2100	110	1170	43	52	20
SIM BTN 16W 865 L1200 SL V3 20X1 OSRAM	4062172048071	Cold white	220-240	16	50 / 60	6500	2100	110	1170	43	52	20
SIM BTN 33W 840 L1200 SL V3 20X1 OSRAM	4062172048040	Neutral white	220-240	33	50 / 60	4000	4300	110	1170	43	52	20
SIM BTN 33W 865 L1200 SL V3 20X1 OSRAM	4062172048057	Cold white	220-240	33	50 / 60	6500	4300	110	1170	43	52	20

Technical data subject to variation and change without notice.

Traxon e:cue

Sales enquiry: [Traxon.ecue.newsletter@osram.com](mailto:Traxon.ecue.newsletter@osram.com)

[www.traxontechnologies.com](http://www.traxontechnologies.com)

