



Product Highlights:

- High efficiency, 120lm/W
- Extruded anti-UV high grade polycarbonate housing
- IP65 waterproof and IK08 impact resistance
- 50,000 hours lifetime

Light is sustainable Simplitz® Waterproof

Flexible, sustainable, and easily maintainable solution with slim profile for humid and dusty environments.

Light is OSRAM

OSRAM

Simplitz® Waterproof



Advantages & Benefits

Product options

- Different combination of power options to match different lumen requirements

Highly reliable and full protection

- IP65 waterproof
- IK08 impact resistance
- 650°C glow wire test passed
- Extruded PC housing with anti-UV additives
- 50,000 hours lifetime

Energy saving

- High system efficacy, up to 120 lm/W

Easy installation and maintenance

- Surface and suspended mounting
- Slim profile, suitable for limited space


Visual comfort

- No LED hot spot

Applications

- General indoor lightings
- Wet and dusty environments
- Industrial areas
- Car parking areas

Photometrics



Dimensions



	17W	33W	28W	50W
L	1200mm	1200mm	1500mm	1500mm
W	57mm	57mm	57mm	57mm
H	67mm	67mm	67mm	67mm

Simplitz® Waterproof series is a flexible, sustainable, and easily maintainable solution with slim profile for humid and dusty environments. It is well-protected against water, dust and impact by extruded anti-UV high grade polycarbonate housing. Installation and maintenance are made easily with the dedicated structure design and flexible surface/suspended mounting options.

Product Reference	Ordering Code (EAN40)		V	W	Hz	K	lm	°	l [mm]	b [mm]	h [mm]	
SIM WP 17W 840 L1200 GY 6X1 OSRAM	4052899587717	Neutral white	220-240	17	50 / 60	4000	2000	110	1200	57	67	6
SIM WP 17W 865 L1200 GY 6X1 OSRAM	4052899587731	Cold white	220-240	17	50 / 60	6500	2000	110	1200	57	67	6
SIM WP 33W 840 L1200 GY 6X1 OSRAM	4052899587755	Neutral white	220-240	33	50 / 60	4000	4000	110	1200	57	67	6
SIM WP 33W 865 L1200 GY 6X1 OSRAM	4052899587779	Cold white	220-240	33	50 / 60	6500	4000	110	1200	57	67	6
SIM WP 28W 840 L1500 GY 6X1 OSRAM	4052899587793	Neutral white	220-240	28	50 / 60	4000	3400	110	1500	57	67	6
SIM WP 28W 865 L1500 GY 6X1 OSRAM	4052899587816	Cold white	220-240	28	50 / 60	6500	3400	110	1500	57	67	6
SIM WP 50W 840 L1500 GY 6X1 OSRAM	4052899587830	Neutral white	220-240	50	50 / 60	4000	6000	110	1500	57	67	6
SIM WP 50W 865 L1500 GY 6X1 OSRAM	4052899587854	Cold white	220-240	50	50 / 60	6500	6000	110	1500	57	67	6

Technical data subject to variation and change without notice.

OSRAM Lighting Solutions Asia Pacific

Sales enquiry: lighting.solutions.apac@osram.com
www.osram.asia/l

